

TECHNISCHE SPEZIFIKATIONEN

TYP 4000

(INNENVERZÄHNUNG)

| Zeichnungsnummer | Dz (mm) | Dn (mm) | H (mm) | Lz (mm) | Ln (mm) | n | B (mm) | M (mm) | O (mm) | U (mm) | H1 (mm) | H2 (mm) | Hu (mm) | Ho (mm) | d (mm) | m (mm) | z | x.m (mm) | b (mm) | T (kg) |
|-------------------------------|---------|-------------|--------|-------------|---------|-----------|--------|-----------|--------|-------------|---------|-----------|---------|-----------|--------|-----------|------|-------------|--------|------------|
| 4050.20.25.0-0.1360.00 | 1460 | 1180 | 102 | 1425 | 1270 | 36 | 22 | 20 | 1337 | 1342 | 76 | 96 | 6 | 26 | 1190 | 10 | 119 | -5,0 | 76 | 336 |
| 4052.20.25.0-0.1600.00 | 1700 | 1404 | 102 | 1665 | 1510 | 42 | 22 | 20 | 1577 | 1582 | 76 | 96 | 6 | 26 | 1416 | 12 | 1416 | -6,0 | 76 | 405 |

| Zeichnungsnummer | Dz (mm) | Dn (mm) | H (mm) | Lz (mm) | Ln (mm) | n | B (mm) | M (mm) | O (mm) | U (mm) | H1 (mm) | H2 (mm) | Hu (mm) | Ho (mm) | d (mm) | m (mm) | z | x.m (mm) | b (mm) | T (kg) |
|-------------------------------|---------|-------------|--------|-------------|---------|-----------|--------|-----------|--------|-------------|---------|------------|---------|-----------|--------|-----------|-----|-------------|--------|------------|
| 4054.20.30.0-0.1381.00 | 1500 | 1164 | 120 | 1455 | 1275 | 36 | 26 | 24 | 1352 | 1358 | 91 | 114 | 6 | 29 | 1176 | 12 | 98 | -6,0 | 91 | 474 |
| 4056.20.30.0-0.1630.00 | 1750 | 1416 | 120 | 1705 | 1525 | 40 | 26 | 24 | 1602 | 1610 | 91 | 114 | 6 | 29 | 1428 | 12 | 119 | -6,0 | 91 | 558 |
| 4058.20.30.0-0.1800.00 | 1920 | 1568 | 120 | 1875 | 1695 | 48 | 26 | 24 | 1771 | 1777 | 91 | 114 | 6 | 29 | 1582 | 14 | 113 | -7,0 | 91 | 643 |
| 4060.20.30.0-0.1995.00 | 2115 | 1764 | 120 | 2070 | 1890 | 48 | 26 | 24 | 1966 | 1972 | 91 | 114 | 6 | 29 | 1778 | 14 | 127 | -7,0 | 91 | 716 |
| 4062.20.30.0-0.2330.00 | 2450 | 2100 | 120 | 2405 | 2225 | 54 | 26 | 24 | 2301 | 2307 | 91 | 114 | 6 | 29 | 2114 | 14 | 151 | -7,0 | 91 | 839 |
| 4064.20.30.0-0.2538.00 | 2660 | 2228 | 120 | 2615 | 2430 | 60 | 26 | 24 | 2509 | 2515 | 91 | 114 | 6 | 29 | 2304 | 16 | 144 | -8,0 | 91 | 963 |

| Zeichnungsnummer | Dz (mm) | Dn (mm) | H (mm) | Lz (mm) | Ln (mm) | n | B (mm) | M (mm) | O (mm) | U (mm) | H1 (mm) | H2 (mm) | Hu (mm) | Ho (mm) | d (mm) | m (mm) | z | x.m (mm) | b (mm) | T (kg) |
|-------------------------------|---------|-------------|--------|-------------|---------|-----------|--------|-----------|--------|-------------|---------|------------|---------|-----------|--------|-----------|-----|-------------|--------|-------------|
| 4066.20.35.0-0.1960.00 | 2090 | 1722 | 138 | 2045 | 1850 | 52 | 26 | 24 | 1926 | 1931 | 104 | 132 | 6 | 34 | 1736 | 14 | 124 | -7,0 | 104 | 851 |
| 4068.20.35.0-0.2500.00 | 2630 | 2254 | 138 | 2585 | 2385 | 66 | 26 | 24 | 2466 | 2471 | 104 | 132 | 6 | 34 | 2268 | 14 | 162 | -7,0 | 104 | 1112 |
| 4070.20.35.0-0.2690.00 | 2820 | 2432 | 138 | 2775 | 2580 | 72 | 26 | 24 | 2656 | 2661 | 104 | 132 | 6 | 34 | 2448 | 16 | 153 | -8,0 | 104 | 1225 |

| Zeichnungsnummer | Dz (mm) | Dn (mm) | H (mm) | Lz (mm) | Ln (mm) | n | B (mm) | M (mm) | O (mm) | U (mm) | H1 (mm) | H2 (mm) | Hu (mm) | Ho (mm) | d (mm) | m (mm) | z | x.m (mm) | b (mm) | T (kg) |
|-------------------------------|---------|-------------|--------|-------------|---------|-----------|--------|-----------|--------|-------------|---------|------------|---------|-----------|--------|-----------|-----|-------------|--------|-------------|
| 4072.20.40.0-0.2199.00 | 2350 | 1920 | 156 | 2295 | 2065 | 52 | 33 | 30 | 2168 | 2164 | 117 | 150 | 6 | 39 | 1936 | 16 | 121 | -8,0 | 117 | 1238 |
| 4074.20.40.0-0.2622.00 | 2770 | 2336 | 156 | 2715 | 2485 | 60 | 33 | 30 | 2590 | 2587 | 117 | 150 | 6 | 39 | 2352 | 16 | 147 | -8,0 | 117 | 1495 |
| 4076.20.40.0-0.2950.00 | 3100 | 2646 | 156 | 3045 | 2815 | 60 | 33 | 30 | 2918 | 2915 | 117 | 150 | 6 | 39 | 2664 | 18 | 148 | -9,0 | 117 | 1764 |
| 4078.20.40.0-0.3300.00 | 3450 | 3006 | 156 | 3395 | 3165 | 66 | 33 | 30 | 3268 | 3265 | 117 | 150 | 6 | 39 | 3024 | 18 | 168 | -9,0 | 117 | 1935 |

TECHNISCHE SPEZIFIKATIONEN TYP 4000 (INNENVERZÄHNUNG)

| Zeichnungsnummer | Dz (mm) | Dn (mm) | H (mm) | Lz (mm) | Ln (mm) | n | B (mm) | M (mm) | O (mm) | U (mm) | H1 (mm) | H2 (mm) | Hu (mm) | Ho (mm) | d (mm) | m (mm) | z | x.m (mm) | b (mm) | T (kg) |
|-------------------------------|---------|---------|--------|---------|---------|----|--------|--------|--------|--------|---------|---------|---------|---------|--------|--------|-----|----------|--------|--------|
| 4080.20.45.0-0.2940.00 | 3100 | 2656 | 175 | 3045 | 2800 | 66 | 33 | 30 | 2903 | 2900 | 132 | 168 | 7 | 43 | 2672 | 16 | 167 | -8,0 | 132 | 1950 |
| 4088.20.45.0-0.3400.00 | 3560 | 3080 | 175 | 3505 | 3260 | 72 | 33 | 30 | 3363 | 3358 | 132 | 168 | 7 | 43 | 3100 | 20 | 155 | -10,0 | 132 | 2435 |

| Zeichnungsnummer | Dz (mm) | Dn (mm) | H (mm) | Lz (mm) | Ln (mm) | n | B (mm) | M (mm) | O (mm) | U (mm) | H1 (mm) | H2 (mm) | Hu (mm) | Ho (mm) | d (mm) | m (mm) | z | x.m (mm) | b (mm) | T (kg) |
|-------------------------------|---------|---------|--------|---------|---------|----|--------|--------|--------|--------|---------|---------|---------|---------|--------|--------|-----|----------|--------|--------|
| 4082.20.50.0-0.2559.00 | 2725 | 2250 | 185 | 2670 | 2410 | 60 | 33 | 30 | 2522 | 2524 | 138 | 178 | 7 | 47 | 2268 | 18 | 126 | -9,0 | 138 | 1892 |
| 4084.20.50.0-0.3520.00 | 3685 | 3200 | 185 | 3630 | 3370 | 78 | 33 | 30 | 3482 | 3485 | 138 | 178 | 7 | 47 | 3220 | 20 | 161 | -10,0 | 138 | 2657 |
| 4086.20.50.0-0.3739.00 | 3905 | 3420 | 185 | 3850 | 3590 | 84 | 33 | 30 | 3701 | 3704 | 138 | 178 | 7 | 47 | 3440 | 20 | 172 | -10,0 | 138 | 2823 |
| 4090.20.50.0-0.3839.00 | 4005 | 3520 | 185 | 395 | 3690 | 84 | 33 | 30 | 3801 | 3804 | 138 | 178 | 7 | 47 | 3540 | 20 | 177 | -10,0 | 138 | 2905 |

