

TECHNISCHE SPEZIFIKATIONEN

TYP 5000

(INNENVERZÄHNUNG)

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5008.20.16.0-1.0400.00	475	304	55	448	352	16	13,5	12	402	398	46	46	9	9	308	4	77	-2,0	46	31
5010.20.16.0-1.0450.00	531	345	55	500	400	16	15,5	14	452	448	46	46	9	9	350	5	70	-2,5	46	40
5012.20.16.0-1.0560.00	641	455	55	610	510	20	15,5	14	562	558	46	46	9	9	460	5	92	-2,5	46	49
5014.20.16.0-1.0630.00	717	516	55	682	578	20	17,5	16	632	628	46	46	9	9	522	6	87	-3,0	46	59

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5024.20.20.0-1.0450.00	536	336	62	505	395	16	15,5	14	452	448	53	53	9	9	342	6	57	-3,0	53	48
5026.20.20.0-1.0560.00	646	444	62	615	505	20	15,5	14	562	558	53	53	9	9	450	6	75	-3,0	53	60
5028.20.20.0-1.0630.00	722	496	62	687	573	20	17,5	16	632	628	53	53	9	9	504	8	63	-4,0	53	75
5030.20.20.0-1.0710.00	802	576	62	767	653	24	17,5	16	712	708	53	53	9	9	584	8	73	-4,0	53	84

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5040.20.25.0-1.0764.00	866	636	73	830	698	24	17,5	16	766	762	64	64	9	9	642	6	107	-3,0	64	113
5042.20.25.0-1.0886.00	988	744	73	952	820	30	17,5	16	888	884	64	64	9	9	752	8	94	-4,0	64	138
5044.20.25.0-1.0980.00	1082	840	73	1046	914	30	17,5	16	982	978	64	64	9	9	848	8	106	-4,0	64	152
5046.20.25.0-1.1077.00	1179	920	73	1143	1011	36	17,5	16	1079	1075	64	64	9	9	930	10	93	-5,0	64	177

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5056.20.25.0-1.1120.00	1232	960	73	1188	1052	36	22	20	1122	1118	64	64	9	9	970	10	97	-5,0	64	192
5058.20.25.0-1.1180.00	1292	1020	73	1248	1112	36	22	20	1182	1178	64	64	9	9	1030	10	103	-5,0	64	202
5060.20.25.0-1.1250.00	1362	1090	73	1318	1182	40	22	20	1252	1248	64	64	9	9	1100	10	110	-5,0	64	213
5062.20.25.0-1.1320.00	1432	1140	73	1388	1252	40	22	20	1322	1318	64	64	9	9	1152	12	96	-6,0	64	240

TECHNISCHE SPEZIFIKATIONEN

TYP 5000

(INNENVERZÄHNUNG)

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5072.20.28.0-1.1400.00	1534	1200	80	1482	1318	36	26	24	1402	1398	71	71	9	9	1212	12	101	-6,0	71	330
5074.20.28.0-1.1500.00	1634	1308	80	1582	1418	40	26	24	1502	1498	71	71	9	9	1320	12	110	-6,0	71	343
5076.20.28.0-1.1600.00	1734	1386	80	1682	1518	40	26	24	1602	1598	71	71	9	9	1400	14	100	-7,0	71	391
5078.20.28.0-1.1700.00	1834	1498	80	1782	1618	44	26	24	1702	1698	71	71	9	9	1512	14	108	-7,0	71	398

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5088.20.36.0-1.1700.00	1871	1456	100	1805	1595	32	33	30	1702	1698	90	90	10	10	1470	14	105	-7,0	90	636
5090.20.36.0-1.1800.00	1971	1554	100	1905	1695	36	33	30	1802	1798	90	90	10	10	1568	14	112	-7,0	90	675
5092.20.36.0-1.1900.00	2071	1652	100	2005	1795	36	33	30	1902	1898	90	90	10	10	1666	14	119	-7,0	90	720
5094.20.36.0-1.2000.00	2171	1764	100	2105	1895	40	33	30	2002	1998	90	90	10	10	1778	14	127	-7,0	90	731

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5104.20.40.0-1.2000.00	2176	1744	108	2110	1890	42	33	30	2003	1997	98	98	10	10	1760	16	110	-8,0	98	832
5106.20.40.0-1.2128.00	2304	1872	108	2238	2018	48	33	30	2113	2125	98	98	10	10	1888	16	118	-8,0	98	882
5108.20.40.0-1.2240.00	2416	1984	108	2350	2130	48	33	30	2243	2237	98	98	10	10	2000	16	125	-8,0	98	932
5110.20.40.0-1.2368.00	2544	2112	108	2478	2258	56	33	30	2371	2365	98	98	10	10	2128	16	133	-8,0	98	980

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5120.20.45.0-1.2240.00	2423	1962	119	2357	2123	48	33	30	2243	2237	109	109	10	10	1980	18	110	-9,0	109	1100
5122.20.45.0-1.2366.00	2549	2088	119	2483	2249	52	33	30	2369	2363	109	109	10	10	2106	18	117	-9,0	109	1160
5124.20.45.0-1.2510.00	2693	2232	119	2627	2393	56	33	30	2513	3507	109	109	10	10	2250	18	125	-9,0	109	1231
5126.20.45.0-1.2645.00	2837	2376	119	2771	2537	60	33	30	2657	2651	109	109	10	10	2394	18	133	-9,0	109	1302

TECHNISCHE SPEZIFIKATIONEN

TYP 5000

(INNENVERZÄHNUNG)

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5136.20.50.0-1.2500.00	2691	2200	130	2625	2375	60	33	30	2503	2497	120	120	10	10	2220	20	111	-10,0	120	1423
5138.20.50.0-1.2660.00	2851	2360	130	2785	2535	64	33	30	2663	2657	120	120	10	10	2380	20	119	-10,0	120	1515
5140.20.50.0-1.2800.00	2691	2500	130	2925	2675	72	33	30	2803	2797	120	120	10	10	2520	20	126	-10,0	120	1588
5142.20.50.0-1.3000.00	3191	2700	130	3125	2875	76	33	30	3003	2997	120	120	10	10	2720	20	136	-10,0	120	1706

