

TECHNISCHE SPEZIFIKATIONEN

TYP 7000

(INNENVERZÄHNUNG)

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
7010.20.20.0-1.1250.00	1397	1032	132	1345	1145	36	26	24	1219	1218	106	123	9	26	1044	12	87	-6	106	539
7012.20.20.0-1.1400.00	1547	1162	132	1495	1295	36	26	24	1396	1368	106	123	9	26	1176	14	84	-7	106	630
7014.20.20.0-1.1600.00	1747	1372	132	1695	1495	40	26	24	1569	1568	106	123	9	26	1386	14	99	-7	106	705
7016.20.20.0-1.1800.00	1947	1552	132	1895	1695	46	26	24	1769	1768	106	123	9	26	1568	16	98	-8	106	829
7018.20.20.0-1.2000.00	2147	1760	132	2095	1895	54	26	24	1969	1968	106	123	9	26	1776	16	111	-8	106	902

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
7030.20.25.0-1.1800.00	1981	1520	147	1915	1675	36	33	30	1763	1774	117	138	9	30	1536	16	96	-8	117	1101
7032.20.25.0-1.2000.00	2181	1728	147	2115	1875	44	33	30	1963	1974	117	138	9	30	1744	16	109	-8	117	1202
7034.20.25.0-1.2240.00	2421	1944	147	2355	2115	48	33	30	2203	2214	117	138	9	30	1962	18	109	-9	117	1406
7036.20.25.0-1.2500.00	2681	2214	147	2615	2375	54	33	30	2463	2474	117	138	9	30	2232	18	124	-9	117	1545
7038.20.25.0-1.2800.00	2981	2500	147	2915	2675	60	33	30	2763	2774	117	138	9	30	2520	20	126	-10	117	1767

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
7050.20.32.0-1.2240.00	2458	1908	181	2380	2085	40	39	36	2199	2210	139	172	9	42	1926	18	107	-9	139	2010
7052.20.32.0-1.2500.00	2718	2178	181	2640	2345	44	39	36	2459	2470	139	172	9	42	2196	18	122	-9	139	2210
7054.20.32.0-1.2800.00	3018	2460	181	2940	2645	48	39	36	2759	2770	139	172	9	42	2480	20	124	-10	139	2542
7056.20.32.0-1.3150.00	3368	2820	181	3290	2995	56	39	36	3109	3120	139	172	9	42	2840	20	142	-10	139	2807
7058.20.40.0-1.2800.00	3038	2460	220	2960	2635	48	39	36	2750	2763	170	210	10	50	2480	20	124	-40	170	3213
7060.20.40.0-1.3150.00	3388	2794	220	3310	2985	56	39	36	3100	3113	170	210	10	50	2816	22	128	-11	170	3683
7062.20.40.0-1.3550.00	3788	3190	220	3710	3385	66	39	36	3500	3513	170	210	10	50	3212	22	146	-11	170	4171
7064.20.40.0-1.4000.00	4238	3624	220	4160	3835	72	39	36	3950	3963	170	210	10	50	3648	24	152	-12	170	4810
7066.20.40.0-1.4500.00	4738	4128	220	4660	4335	84	39	36	4450	4463	170	210	10	50	4152	24	173	-12	170	5367

