

TECHNISCHE SPEZIFIKATIONEN

TYP 4000

(AUSSENVERZÄHNUNG)

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)	t (mm)	Zn (mm)	hu (mm)
4008.30.20.0-0.0755.00	862,8	679	82	800	706	24	17,5	16	797	771	58	78	4	24	852	6	142	+0,0	50	10	35	833	8
4010.30.20.0-0.0971.00	1078,4	895	82	1015	922	30	17,5	16	1012	987	58	78	4	24	1064	8	133	+0,0	50	128	35	1024	8
4012.30.20.0-0.1220.00	1342,4	1140	82	1270	1170	48	17,5	16	1261	1238	58	78	4	24	1320	8	165	+4,0	50	178	35	-	-
4014.30.20.0-0.1385.00	1502,4	1305	82	1435	1335	54	17,5	16	1426	1403	58	78	4	24	1480	8	185	+4,0	50	201	35	-	-

