

TECHNISCHE SPEZIFIKATIONEN TYP 4000 (INNENVERZÄHNUNG)

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
4802.20.22.0-0.0625.00	705	504	92	675	575	32	18	16	627	623	83	83	9	9	520	8	65	0	83	95
4804.20.22.0-0.0897.00	973	786	97	944	850	36	18	16	899	895	88	88	9	9	800	8	100	0	88	141
4806.20.22.0-0.1087.00	1172	962	97	1134	1040	36	18	16	1089	1085	88	88	9	9	980	10	98	0	88	193
4808.20.25.0-0.1100.00	1200	963,5	110	1160	1040	36	22	20	1102	1098	96	96	14	14	980	10	98	0	96	239
4810.20.30.0-0.1220.00	1345	1061,6	108	1290	1150	40	22	20	1222	1218	98	98	10	10	1080	10	108	0	98	331
4812.20.30.0-0.1347.00	1470	1183	108	1425	1270	40	22	22	1350	1344	98	98	10	10	1200	10	120	0	98	371
4814.20.30.0-0.1385.00	1530	1186	144	1480	1290	48	26	24	1388	1382	134	134	10	10	1200	10	120	0	134	612
4816.20.30.0-0.1615.00	1750	1418,4	120	1705	1525	40	26	24	1618	1612	110	105	10	15	1200	12	120	0	110	572
4818.20.30.0-0.2003.00	2178	1776	144	2108	1898	72	30	27	2005	2000	134	134	10	10	1800	12	150	0	134	1062

