

TECHNISCHE SPEZIFIKATIONEN TYP 2000 (AUSSENVERZÄHNUNG)

| Zeichnungsnummer | Dl (mm) | Dz (mm) | Dn (mm) | H (mm) | Lz (mm) | Ln (mm) | nz | B/M (mm) | nn | B/M (mm) | t (mm) | O (mm) | U (mm) | A (mm) | C (mm) | Hu (mm) | Ho (mm) | d (mm) | m (mm) | z | b (mm) | T (kg) |
|-------------------------------|------------|------------|------------|-----------|------------|------------|----|-------------|----|-------------|-----------|-----------|-----------|-----------|-----------|------------|------------|-----------|-----------|-----|-----------|-----------|
| 2054.30.30.0-0.0955.00 | 955 | 1098 | 805 | 90 | 1016 | 845 | 30 | M20 | 30 | 22 | 40 | 956,5 | 953,5 | - | 893 | 19 | - | 1080 | 9 | 120 | 71 | 165 |
| 2056.30.30.0-0.1055.00 | 1055 | 1200 | 905 | 90 | 1116 | 945 | 30 | M20 | 30 | 22 | 40 | 1056,5 | 1053,5 | - | 993 | 19 | - | 1180 | 10 | 118 | 71 | 183 |
| 2058.30.30.0-0.1155.00 | 1155 | 1300 | 1005 | 90 | 1216 | 1045 | 36 | M20 | 30 | 22 | 40 | 1156,5 | 1153,5 | - | 1093 | 19 | - | 1280 | 10 | 128 | 71 | 200 |
| 2060.30.30.0-0.1255.00 | 1255 | 1400 | 1105 | 90 | 1316 | 1145 | 42 | M20 | 30 | 22 | 40 | 1256,5 | 1253,5 | - | 1193 | 19 | - | 1380 | 10 | 138 | 71 | 216 |
| 2062.30.30.0-0.1355.00 | 1355 | 1500 | 1205 | 90 | 1416 | 1245 | 42 | M20 | 30 | 22 | 40 | 1356,5 | 1353,5 | - | 1293 | 19 | - | 1480 | 10 | 148 | 71 | 234 |
| 2064.30.30.0-0.1455.00 | 1455 | 1600 | 1305 | 90 | 1516 | 1345 | 48 | M20 | 30 | 22 | 40 | 1456,5 | 1453,5 | - | 2393 | 19 | - | 1580 | 10 | 158 | 71 | 250 |

